

CORE LINERS AND ACCESSORIES

Clear UPVC core liners are compatible with most window sampling core barrels. They are used to keep core samples intact. They can also be used to minimise cross contamination between samples in contaminated soil investigations.

- Wall thickness = 1 mm
- Tolerance of Length +/- 5.0mm
- Tolerance of O.D. (< 8.7mm) +/- 1.5mm
- Tolerance of O.D. (> 87mm) +/- 2.0mm



Applications: • Geotechnical investigation • Environmental investigation

Outside Diameter mm	Core Reference	Length m	Core Liner Part Number	Cap Part Number
35		1	GCL35	GCL35C
37		1	GCL37	GCL37C
47		1	GCL47	GCL47C
53		1	GCL53	GCL53C
55		1	GCL55	GCL55C
57		1	GCL57	GCL57C
65		1	GCL65	GCL65C
67		1	GCL67	GCL67C
75		1	GCL75	GCL75C
77		1	GCL77	GCL77C
79	T6-H	3	GCL783	
87		1	GCL87	GCL87C
94.5	T6-116	1.6	GCL9416	
94.5	T6-116	3	GCL94/3M T6-116	
97		1	GCL97	GCL97
101		1	GCL101	GCL101
102		1	GCL102	GCL102
113	SWF	1.6	GC113.6	
113	SWF	3	GCL113/SWF3	

U100 Samplers

U100 liner is a tough and durable PVC plastic liner. Suitable for sampling undisturbed soil



CORE LINER BOXES

Core liner boxes store retrieved core samples, allowing safe transportation. They are available in wood or PVC



Core Liner Size	No. of Core Liners	Length	Wooden Box	PVC Box
mm		m	Part Number	Part Number
88	5	1		GCP1PS
95	2	1.5	GCB1.5	
95	3	1	GCB1	
129	3	1		GCB1P3

CORE CUTTERS & SEALING WAX

A core cutter is the safe way to cut core liners, swiftly and efficiently.

