

UPVC Wellscreen and Well Liners

Our UPVC (unplasticised polyvinyl chloride) liners are PFAS (per and polyfluorinated alkyl substances) free. The wellscreens are male/female threaded with various machined slot sizes to allow for ground conditions.

UPVC is the most ideal material for manufacturing well pipes as it is impervious to corrosion and chemical action, easy-to-handle and install, lightweight, non-toxic and non-conductive. Its long service life makes it an economical choice.

The well liners are suitable for use in water abstraction projects and are approved under the Water Regulations Approval Scheme (WRAS), Approval Number: [2309549](#).

The testing procedure confirms that the well screens and casings are suitable for contact with wholesome water for domestic purposes having met the requirements of BS6920-1:2000 and/or 2014 'Suitability of non-metallic products for use in contact with water intended for human consumption with regard to their effect on the quality of the water.'

The approval is valid until September 2028

Available in 1 m and 3 m lengths with various slot sizes



Nominal Diameter		Outside Diameter	Wall Thickness	Inside Diameter	Outside Diameter Over Connection
mm	inch	mm	mm	mm	mm
35	1 1/4	42	3.5	33	46
50	2	60	4	50	65
80	3	88	4	78	93
100	4	113	5	101	119
115	4 1/2	125	5	113	131
125	5	140	6.5	125	149
150	6	165	5.7	152	172
175	7	200	7.0	184	210
200	8	225	7.6	207	236